# [ SEQ CHAPTER \h \r 1]Statement of Basis of the Federal Operating Permit

Indorama Ventures Oxides LLC

Site Name: Port Neches Operations Area Name: E4 Units Physical Location: 2701 Spur 136 Nearest City: Port Neches County: Jefferson

> Permit Number: O2287 Project Type: Renewal

The North American Industry Classification System (NAICS) Code: 32511
NAICS Name: Petrochemical Manufacturing

This Statement of Basis sets forth the legal and factual basis for the draft permit conditions in accordance with 30 TAC §122.201(a)(4). Per 30 TAC §§ 122.241 and 243, the permit holder has submitted an application under § 122.134 for permit renewal. This document may include the following information:

A description of the facility/area process description;

A basis for applying permit shields;

A list of the federal regulatory applicability determinations;

A table listing the determination of applicable requirements;

A list of the New Source Review Requirements;

The rationale for periodic monitoring methods selected;

The rationale for compliance assurance methods selected;

A compliance status; and

A list of available unit attribute forms.

Prepared on: April 15, 2020

# Operating Permit Basis of Determination

#### **Permit Area Process Description**

E4 Unit - Ethanolamine Production: The E4 unit produces ethanolamines including MEA, TEA, DEA, N-1, and crude DEA. Ethanolamines are made by reacting ammonia and ethylene oxide. The unconverted ammonia is removed by stripping and the ethanolamines are separated by fractionation under vacuum distillation. The process utilizes a vent scrubber to remove excess ammonia. The products and byproducts are stored in fixed roof storage tanks and loaded into tank cars, tank wagons, barges and drums. There is a closed system tank car/tank wagon unloading rack for ammonia. There is a tank car/tank truck loading rack for products equipped with a scrubber.

Wastewater streams that contain significant levels of VOC's are pre-stripped at the unit facility level and sent to a control device before being routed to the Joint Wastewater Treatment Plant.

#### FOPs at Site

The "application area" consists of the emission units and that portion of the site included in the application and this permit. Multiple FOPs may be issued to a site in accordance with 30 TAC § 122.201(e). When there is only one area for the site, then the application information and permit will include all units at the site. Additional FOPs that exist at the site, if any, are listed below.

Additional FOPs: O1320, O2286, O2288, O3056

# **Major Source Pollutants**

The table below specifies the pollutants for which the site is a major source:

Major Pollutants	VOC, SO2, NOX, HAPS, CO

#### Reading State of Texas's Federal Operating Permit

The Title V Federal Operating Permit (FOP) lists all state and federal air emission regulations and New Source Review (NSR) authorizations (collectively known as "applicable requirements") that apply at a particular site or permit area (in the event a site has multiple FOPs). **The FOP does not authorize new emissions or new construction activities.** The FOP begins with an introductory page which is common to all Title V permits. This page gives the details of the company, states the authority of the issuing agency, requires the company to operate in accordance with this permit and 30 Texas Administrative Code (TAC) Chapter 122, requires adherence with NSR requirements of 30 TAC Chapter 116, and finally indicates the permit number and the issuance date.

This is followed by the table of contents, which is generally composed of the following elements. Not all permits will have all of the elements.

- General Terms and Conditions
- Special Terms and Conditions
  - Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting
  - Additional Monitoring Requirements
  - New Source Review Authorization Requirements
  - o Compliance Requirements
  - Protection of Stratosphere Ozone
  - Permit Location
  - Permit Shield (30 TAC § 122.148)
- Attachments
  - o Applicable Requirements Summary

Page [ PAGE ] of [ NUMPAGES ]

- Unit Summary
- Applicable Requirements Summary
- Additional Monitoring Requirements
- o Permit Shield
- New Source Review Authorization References
- o Compliance Plan
- o Alternative Requirements
- Appendix A
  - o Acronym list

#### General Terms and Conditions

The General Terms and Conditions are the same and appear in all permits. The first paragraph lists the specific citations for 30 TAC Chapter 122 requirements that apply to all Title V permit holders. The second paragraph describes the requirements for record retention. The third paragraph provides details for voiding the permit, if applicable. The fourth paragraph states that the permit holder shall comply with the requirements of 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit. The fifth paragraph provides details on submission of reports required by the permit.

### Special Terms and Conditions

Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting. The TCEQ has designated certain applicable requirements as site-wide requirements. A site-wide requirement is a requirement that applies uniformly to all the units or activities at the site. Units with only site-wide requirements are addressed on Form OP-REQ1 and are not required to be listed separately on a OP-UA Form or Form OP-SUM. Form OP-SUM must list all units addressed in the application and provide identifying information, applicable OP-UA Forms, and preconstruction authorizations. The various OP-UA Forms provide the characteristics of each unit from which applicable requirements are established. Some exceptions exist as a few units may have both site-wide requirements and unit specific requirements.

Other conditions. The other entries under special terms and conditions are in general terms referring to compliance with the more detailed data listed in the attachments.

#### Attachments

Applicable Requirements Summary. The first attachment, the Applicable Requirements Summary, has two tables, addressing unit specific requirements. The first table, the Unit Summary, includes a list of units with applicable requirements, the unit type, the applicable regulation, and the requirement driver. The intent of the requirement driver is to inform the reader that a given unit may have several different operating scenarios and the differences between those operating scenarios.

The applicable requirements summary table provides the detailed citations of the rules that apply to the various units. For each unit and operating scenario, there is an added modifier called the "index number," detailed citations specifying monitoring and testing requirements, recordkeeping requirements, and reporting requirements. The data for this table are based on data supplied by the applicant on the OP-SUM and various OP-UA forms.

Additional Monitoring Requirement. The next attachment includes additional monitoring the applicant must perform to ensure compliance with the applicable standard. Compliance assurance monitoring (CAM) is often required to provide a reasonable assurance of compliance with applicable emission limitations/standards for large emission units that use control devices to achieve compliance with applicant requirements. When necessary, periodic monitoring (PM) requirements are specified for certain parameters (i.e. feed rates, flow rates, temperature, fuel type and consumption, etc.) to determine if a term and condition or emission unit is operating within specified limits to control emissions. These additional monitoring approaches may be required for two reasons. First, the applicable rules do not adequately specify monitoring requirements (exception- Maximum Achievable Control Technology Standards (MACTs) generally have sufficient monitoring), and second, monitoring may be required to fill gaps in the monitoring requirements of certain applicable requirements. In situations where the NSR permit is the applicable requirement requiring extra monitoring for a

Page 3 of 20

specific emission unit, the preferred solution is to have the monitoring requirements in the NSR permit updated so that all NSR requirements are consolidated in the NSR permit.

Permit Shield. A permit may or may not have a permit shield, depending on whether an applicant has applied for, and justified the granting of, a permit shield. A permit shield is a special condition included in the permit document stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirement(s) or specified applicable state-only requirement(s).

New Source Review Authorization References. All activities which are related to emissions in the state of Texas must have a NSR authorization prior to beginning construction. This section lists all units in the permit and the NSR authorization that allowed the unit to be constructed or modified. Units that do not have unit specific applicable requirements other than the NSR authorization do not need to be listed in this attachment. While NSR permits are not physically a part of the Title V permit, they are legally incorporated into the Title V permit by reference. Those NSR permits whose emissions exceed certain PSD/NA thresholds must also undergo a Federal review of federally regulated pollutants in addition to review for state regulated pollutants.

Compliance Plan. A permit may have a compliance schedule attachment for listing corrective actions plans for any emission unit that is out of compliance with an applicable requirement.

Alternative Requirements. This attachment will list any alternative monitoring plans or alternative means of compliance for applicable requirements that have been approved by the EPA Administrator and/or the TCEQ Executive Director.

# Appendix A

Acronym list. This attachment lists the common acronyms used when discussing the FOPs.

# Stationary vents subject to 30 TAC Chapter 111, Subchapter A, § 111.111(a)(1)(B) addressed in the Special Terms and Conditions

The site contains stationary vents with a flowrate less than 100,000 actual cubic feet per minute (acfm) and constructed after January 31, 1972 which are limited, over a six-minute average, to 20% opacity as required by 30 TAC § 111.111(a)(1)(B). As a site may have a large number of stationary vents that fall into this category, they are not required to be listed individually in the permit's Applicable Requirement Summary. This is consistent with EPA's White Paper for Streamlined Development of Part 70 Permit Applications, July 10, 1995, that states that requirements that apply identically to emission units at a site can be treated on a generic basis such as source-wide opacity limits.

Periodic monitoring is specified in Special Term and Condition 3 for stationary vents subject to 30 TAC § 111.111(a)(1)(B) to verify compliance with the 20% opacity limit. These vents are not expected to produce visible emissions during normal operation. The TCEQ evaluated the probability of these sources violating the opacity standards and determined that there is a very low potential that an opacity standard would be exceeded. It was determined that continuous monitoring for these sources is not warranted as there would be very limited environmental benefit in continuously monitoring sources that have a low potential to produce visible emissions. Therefore, the TCEQ set the visible observation monitoring frequency for these sources to once per calendar quarter.

The TCEQ has exempted vents that are not capable of producing visible emissions from periodic monitoring requirements. These vents include sources of colorless VOCs, non-fuming liquids, and other materials that cannot produce emissions that obstruct the transmission of light. Passive ventilation vents, such as plumbing vents, are also included in this category. Since this category of vents are not capable of producing opacity due to the physical or chemical characteristics of the emission source, periodic monitoring is not required as it would not yield any additional data to assure compliance with the 20% opacity standard of 30 TAC § 111.111(a)(1)(B).

In the event that visible emissions are detected, either through the quarterly observation or other credible evidence, such as observations from company personnel, the permit holder shall either report a deviation or perform a Test Method 9 observation to determine the opacity consistent with the 6-minute averaging time specified in 30 TAC § 111.111(a)(1)(B). An additional provision is included to monitor combustion sources more frequently than quarterly if alternate fuels are

Page 4 of 20

burned for periods greater than 24 consecutive hours. This will address possible emissions that may arise when switching fuel types.

#### Stationary Vents subject to 30 TAC Chapter 111 not addressed in the Special Terms and Conditions

All other stationary vents subject to 30 TAC Chapter 111 not covered in the Special Terms and Conditions are listed in the permit's Applicable Requirement Summary. The basis for the applicability determinations for these vents are listed in the Determination of Applicable Requirements table.

#### **Federal Regulatory Applicability Determinations**

The following chart summarizes the applicability of the principal air pollution regulatory programs to the permit area:

Regulatory Program	Applicability (Yes/No)
Prevention of Significant Deterioration (PSD)	No
Nonattainment New Source Review (NNSR)	No
Minor NSR	Yes
40 CFR Part 60 - New Source Performance Standards	Yes
40 CFR Part 61 - National Emission Standards for Hazardous Air Pollutants (NESHAPs)	Yes
40 CFR Part 63 - NESHAPs for Source Categories	Yes
Title IV (Acid Rain) of the Clean Air Act (CAA)	No
Title V (Federal Operating Permits) of the CAA	Yes
Title VI (Stratospheric Ozone Protection) of the CAA	Yes
CSAPR (Cross-State Air Pollution Rule)	No
Federal Implementation Plan for Regional Haze (Texas SO <sub>2</sub> Trading Program)	No

#### **Basis for Applying Permit Shields**

An operating permit applicant has the opportunity to specifically request a permit shield to document that specific applicable requirements do not apply to emission units in the permit. A permit shield is a special condition stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements. A permit shield has been requested in the application for specific emission units. For the permit shield requests that have been approved, the basis of determination for regulations that the owner/operator need not comply with are located in the "Permit Shield" attachment of the permit.

Page 5 of 20

#### **Insignificant Activities**

In general, units not meeting the criteria for inclusion on either Form OP-SUM or Form OP-REQ1 are not required to be addressed in the operating permit application. Examples of these types of units include, but are not limited to, the following:

- 1. Office activities such as photocopying, blueprint copying, and photographic processes.
- 2. Sanitary sewage collection and treatment facilities other than those used to incinerate wastewater treatment plant sludge. Stacks or vents for sanitary sewer plumbing traps are also included.
- 3. Food preparation facilities including, but not limited to, restaurants and cafeterias used for preparing food or beverages primarily for consumption on the premises.
- 4. Outdoor barbecue pits, campfires, and fireplaces.
- 5. Laundry dryers, extractors, and tumblers processing bedding, clothing, or other fabric items generated primarily at the premises. This does not include emissions from dry cleaning systems using perchloroethylene or petroleum solvents.
- Facilities storing only dry, sweet natural gas, including natural gas pressure regulator vents.
- 7. Any air separation or other industrial gas production, storage, or packaging facility. Industrial gases, for purposes of this list, include only oxygen, nitrogen, helium, neon, argon, krypton, and xenon.
- 8. Storage and handling of sealed portable containers, cylinders, or sealed drums.
- 9. Vehicle exhaust from maintenance or repair shops.
- 10. Storage and use of non-VOC products or equipment for maintaining motor vehicles operated at the site (including but not limited to, antifreeze and fuel additives).
- 11. Air contaminant detectors and recorders, combustion controllers and shut-off devices, product analyzers, laboratory analyzers, continuous emissions monitors, other analyzers and monitors, and emissions associated with sampling activities. Exception to this category includes sampling activities that are deemed fugitive emissions and under a regulatory leak detection and repair program.
- 12. Bench scale laboratory equipment and laboratory equipment used exclusively for chemical and physical analysis, including but not limited to, assorted vacuum producing devices and laboratory fume hoods.
- 13. Steam vents, steam leaks, and steam safety relief valves, provided the steam (or boiler feedwater) has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
- 14. Storage of water that has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
- 15. Well cellars.
- 16. Fire or emergency response equipment and training, including but not limited to, use of fire control equipment including equipment testing and training, and open burning of materials or fuels associated with firefighting training.
- 17. Crucible or pot furnaces with a brim full capacity of less than 450 cubic inches of any molten metal.
- 18. Equipment used exclusively for the melting or application of wax.
- 19. All closed tumblers used for the cleaning or deburring of metal products without abrasive blasting, and all open tumblers with a batch capacity of 1,000 lbs. or less.
- 20. Shell core and shell mold manufacturing machines.
- 21. Sand or investment molds with a capacity of 100 lbs. or less used for the casting of metals;
- 22. Equipment used for inspection of metal products.
- 23. Equipment used exclusively for rolling, forging, pressing, drawing, spinning, or extruding either hot or cold metals by some mechanical means.
- 24. Instrument systems utilizing air, natural gas, nitrogen, oxygen, carbon dioxide, helium, neon, argon, krypton, and xenon.
- 25. Battery recharging areas.
- 26. Brazing, soldering, or welding equipment.

# **Determination of Applicable Requirements**

The tables below include the applicability determinations for the emission units, the index number(s) where applicable, and all relevant unit attribute information used to form the basis of the applicability determination. The unit attribute information is a description of the physical properties of an emission unit which is used to determine the requirements to

Page 6 of 20

which the permit holder must comply. For more information about the descriptions of the unit attributes specific Unit Attribute Forms may be viewed at [HYPERLINK "http://www.tceq.texas.gov/permitting/air/nav/air all ua forms.html"].

A list of unit attribute forms is included at the end of this document. Some examples of unit attributes include construction date; product stored in a tank; boiler fuel type; etc.. Generally, multiple attributes are needed to determine the requirements for a given emission unit and index number. The table below lists these attributes in the column entitled "Basis of Determination." Attributes that demonstrate that an applicable requirement applies will be the factual basis for the specific citations in an applicable requirement that apply to a unit for that index number. The TCEQ Air Permits Division has developed flowcharts for determining applicability of state and federal regulations based on the unit attribute information in a Decision Support System (DSS). These flowcharts can be accessed via the internet at [ HYPERLINK "http://www.tceq.texas.gov/permitting/air/nav/air\_supportsys.html"]. The Air Permits Division staff may also be contacted for assistance at (512) 239-1250.

The attributes for each unit and corresponding index number provide the basis for determining the specific legal citations in an applicable requirement that apply, including emission limitations or standards, monitoring, recordkeeping, and reporting. The rules were found to apply or not apply by using the unit attributes as answers to decision questions found in the flowcharts of the DSS. Some additional attributes indicate which legal citations of a rule apply. The legal citations that apply to each emission unit may be found in the Applicable Requirements Summary table of the draft permit. There may be some entries or rows of units and rules not found in the permit, or if the permit contains a permit shield, repeated in the permit shield area. These are sets of attributes that describe negative applicability, or; in other words, the reason why a potentially applicable requirement does not apply.

If applicability determinations have been made which differ from the available flowcharts, an explanation of the decisions involved in the applicability determination is specified in the column "Changes and Exceptions to RRT." If there were no exceptions to the DSS, then this column has been removed.

The draft permit includes all emission limitations or standards, monitoring, recordkeeping and reporting required by each applicable requirement. If an applicable requirement does not require monitoring, recordkeeping, or reporting, the word "None" will appear in the Applicable Requirements Summary table. If additional periodic monitoring is required for an applicable requirement, it will be explained in detail in the portion of this document entitled "Rationale for Compliance Assurance Monitoring (CAM)/ Periodic Monitoring Methods Selected."

When attributes demonstrate that a unit is not subject to an applicable requirement, the applicant may request a permit shield for those items. The portion of this document entitled "Basis for Applying Permit Shields" specifies which units, if any, have a permit shield.

#### Operational Flexibility

When an emission unit has multiple operating scenarios, it will have a different index number associated with each operating condition. This means that units are permitted to operate under multiple operating conditions. The applicable requirements for each operating condition are determined by a unique set of unit attributes. For example, a tank may store two different products at different points in time. The tank may, therefore, need to comply with two distinct sets of requirements, depending on the product that is stored. Both sets of requirements are included in the permit, so that the permit holder may store either product in the tank.

# **Determination of Applicable Requirements**

Unit ID	Regulation	Index Number	Basis of Determination*
E4FE4144	30 TAC Chapter 115, Storage of VOCs	R5111-0	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			Product Stored = VOC other than crude oil or condensate
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
E4FE4144	40 CFR Part 60, Subpart	60KB-0	Product Stored = Volatile organic liquid
	Kb		Storage Capacity = Capacity is greater than or equal to 10,600 gallons but less than 19,813 gallons (capacity is greater than 40,000 liters but less than or equal to 75,000 liters)
E4FE4144	40 CFR Part 63, Subpart	63GT-042	MACT Subpart F/G Applicability = The unit is a Group 2 vessel.
	G		NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.
			NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.
E4TE413	30 TAC Chapter 115, Storage of VOCs	R5112-00g	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			Product Stored = VOC other than crude oil or condensate
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
E4TE414	30 TAC Chapter 115, Storage of VOCs	R5112-00g	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			Product Stored = VOC other than crude oil or condensate
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
E4TE424	30 TAC Chapter 115, Storage of VOCs	R5112-00a	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			Product Stored = VOC other than crude oil or condensate
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
E4TE429	30 TAC Chapter 115, Storage of VOCs	R5112-00a	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.

Unit ID	Regulation	Index Number	Basis of Determination*
			Tank Description = Tank does not require emission controls  Product Stored = VOC other than crude oil or condensate  True Vapor Pressure = True vapor pressure is less than 1.0 psia  Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
E4TE435	30 TAC Chapter 115, Storage of VOCs	R5112-00c	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.  Tank Description = Tank does not require emission controls  Product Stored = VOC other than crude oil or condensate  True Vapor Pressure = True vapor pressure is less than 1.0 psia  Storage Capacity = Capacity is greater than 40,000 gallons
E4TE435	40 CFR Part 60, Subpart Kb	60Kb-22	Product Stored = Volatile organic liquid  Storage Capacity = Capacity is greater than or equal to 39,890 gallons (151,000 liters)  Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
E4TE436	30 TAC Chapter 115, Storage of VOCs	R5112-00c	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.  Tank Description = Tank does not require emission controls  Product Stored = VOC other than crude oil or condensate  True Vapor Pressure = True vapor pressure is less than 1.0 psia  Storage Capacity = Capacity is greater than 40,000 gallons
E4TE436	40 CFR Part 60, Subpart Kb	60Kb-22	Product Stored = Volatile organic liquid  Storage Capacity = Capacity is greater than or equal to 39,890 gallons (151,000 liters)  Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
E4TE437	30 TAC Chapter 115, Storage of VOCs	R5112-00c	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.  Tank Description = Tank does not require emission controls  Product Stored = VOC other than crude oil or condensate  True Vapor Pressure = True vapor pressure is less than 1.0 psia  Storage Capacity = Capacity is greater than 40,000 gallons
E4TE437	40 CFR Part 60, Subpart Kb	60Kb-22	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 39,890 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
GRPE4TK1	30 TAC Chapter 115, Storage of VOCs	R5112-00a	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.

Unit ID	Regulation	Index Number	Basis of Determination*
			Tank Description = Tank does not require emission controls
			Product Stored = VOC other than crude oil or condensate
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
GRPE4TK1	40 CFR Part 63, Subpart	63GT-042	MACT Subpart F/G Applicability = The unit is a Group 2 vessel.
	G		NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.
			NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.
GRPE4TK2	30 TAC Chapter 115, Storage of VOCs	R5112-00c	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			Product Stored = VOC other than crude oil or condensate
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Storage Capacity = Capacity is greater than 40,000 gallons
GRPE4TK2	40 CFR Part 63, Subpart	63GT-042	MACT Subpart F/G Applicability = The unit is a Group 2 vessel.
	G		NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.
			NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.
GRPE4TK3	30 TAC Chapter 115, Storage of VOCs	R5112-00g	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			Product Stored = VOC other than crude oil or condensate
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
GRPE4TK3	40 CFR Part 63, Subpart	63GT-042	MACT Subpart F/G Applicability = The unit is a Group 2 vessel.
	G		NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.
			NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.
E4LREAC	30 TAC Chapter 115, Loading and Unloading of	R5211-018	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Voc		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
E4LREAC	40 CFR Part 63, Subpart G	63GL-0g2a	Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111).

Unit ID	Regulation	Index Number	Basis of Determination*
			Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.
E4LREAW	30 TAC Chapter 115, Loading and Unloading of	R5211-018	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Voc		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
E4LREAW	40 CFR Part 63, Subpart	63GL-0g2a	Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111).
	G		Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.
RSELDS	40 CFR Part 63, Subpart	63Y-005	Subpart Y Facility Type = Existing onshore loading terminal (located onshore or less than 0.5 miles from shore).
	Y		Ballasting Operations = Operations other than or in addition to ballasting operations are performed at the facility.
			Vapor Pressure = Vapor pressure is greater than or equal to 10.3 kilopascals (1.5 psia) at standard conditions, 20° C and 760 mm Hg.
			Subpart BB Applicability = Marine vessel loading operations are not subject to and complying with 40 CFR Part 61, Subpart BB.
			Material Loaded = Material other than crude oil or gasoline.
			HAP Impurities Only = Marine vessel loading operations at loading berths transfer liquids containing organic hazardous air pollutants other than as impurities.
			Source Emissions = Source with emissions less than 10 and 25 tons.
E4FUG1	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-ALL	SOP/GOP Index No. = Owner/Operator assumes VOC fugitive control requirements for all components subject to 30 TAC Chapter 115, Subchapter D, Division 3 with no alternate control or control device.
E4FUG1	40 CFR Part 63, Subpart H	63H-ALL	SOP Index No. = Owner/Operator assumes fugitive control requirements for all components in VOC or VHAP service subject to 40 CFR Part 63, Subpart H with no alternated control or control device.
E4FE411	30 TAC Chapter 115,	R5121-10	Alternate Control Requirement = Alternate control is not used.
	Vent Gas Controls	ent Gas Controls	Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.
			Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.
			Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.
			Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.

Unit ID	Regulation	Index Number	Basis of Determination*
			40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies one of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.
			Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.
			40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies one of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.
E4FE411	40 CFR Part 63, Subpart G	63GV-100	Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.
			Control Device = Absorber used as a recovery device.
			Overlap = Title 40 CFR Part 63, Subpart G only
			Group 1 = The process vent is a Group 2 process vent.
			Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.
			Halogenated = Vent stream is not halogenated.
			HAP Concentration = HAP concentration is greater than or equal to 50 ppm.
			By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.
			Flow Rate = Flow rate is less than 0.005 scm/min.
			Electing Control = Not electing to control the process vent to the levels required in 40 CFR § 63.113(a)(1) or (a)(2).
			Performance Test = No previous performance test was conducted.
E4FE423	30 TAC Chapter 111,	R1111-0	Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.
	Visible Emissions		Vent Source = The source of the vent is from colorless VOCs, non-fuming liquids, or other sources that are not capable of producing visible emissions. Periodic monitoring to demonstrate compliance is not required.
			Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).
			Construction Date = After January 31, 1972
			Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.
E4FE456	30 TAC Chapter 115,	R5121-10	Alternate Control Requirement = Alternate control is not used.
Vent Gas Controls	Vent Gas Controls	Controls	Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.
			Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.
			Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.
			Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.

Unit ID	Regulation	Index Number	Basis of Determination*
			40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies one of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.
			Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.
			40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies one of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.
E4FE456	40 CFR Part 63, Subpart G	63GV-100	Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.
			Control Device = Condenser used as a recovery device.
			Overlap = Title 40 CFR Part 63, Subpart G only
			Group 1 = The process vent is a Group 2 process vent.
			Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.
			Halogenated = Vent stream is not halogenated.
			HAP Concentration = HAP concentration is greater than or equal to 50 ppm.
			By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.
			Flow Rate = Flow rate is less than 0.005 scm/min.
			Electing Control = Not electing to control the process vent to the levels required in 40 CFR § 63.113(a)(1) or (a)(2).
			Performance Test = No previous performance test was conducted.
E4FE49	30 TAC Chapter 115,	R5121-10	Alternate Control Requirement = Alternate control is not used.
	Vent Gas Controls		Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.
			Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.
			Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.
			Flow Rate or VOC Concentration = Flow rate is greater than or equal to 0.011 scm/min or the VOC concentration is greater than or equal to 500 ppmv.
			40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies one of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.
			Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.
			40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies one of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.

Unit ID	Regulation	Index Number	Basis of Determination*
GRPE4VNT1 30 TAC Chapter 115, Vent Gas Controls		R5121-19	Alternate Control Requirement = Alternate control is not used.
		Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.	
			Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.
			Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.
			Flow Rate or VOC Concentration = Flow rate is less than 0.011 scm/min or the VOC concentration is less than 500 ppmv.
			40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.
			Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.
			40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.
GRPE4VNT1	40 CFR Part 63, Subpart G	63GV-100	Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.
			Control Device = Condenser used as a recovery device.
			Overlap = Title 40 CFR Part 63, Subpart G only
			Group 1 = The process vent is a Group 2 process vent.
			Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.
			Halogenated = Vent stream is not halogenated.
			HAP Concentration = HAP concentration is greater than or equal to 50 ppm.
			By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.
			Flow Rate = Flow rate is less than 0.005 scm/min.
			Electing Control = Not electing to control the process vent to the levels required in 40 CFR § 63.113(a)(1) or (a)(2).
			Performance Test = No previous performance test was conducted.
GRPTKVNT	30 TAC Chapter 111,	R1111-0	Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.
Visible Emissions	Visible Emissions	ons	Vent Source = The source of the vent is from colorless VOCs, non-fuming liquids, or other sources that are not capable of producing visible emissions. Periodic monitoring to demonstrate compliance is not required.
			Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).
			Construction Date = After January 31, 1972
			Effluent Flow Rate = Effluent flow rate is less than 100,000 actual cubic feet per minute.

Unit ID	Regulation	Index Number	Basis of Determination*
PROE4HON	40 CFR Part 63, Subpart	63F-009	Applicable Chemicals = The chemical manufacturing process unit manufactures, as a primary product, one or more of the chemicals listed in 40 CFR § 63.100(b)(1)(i) or 40 CFR § 63.100(b)(1)(ii).
			Intervening Cooling Fluid = There is no intervening cooling fluid containing less than 5 percent by weight of total HAPs listed in Table 4 of 40 CFR Part 63, Subpart F, between the process and cooling water.
			Table 2 HAP = The chemical manufacturing process unit uses as a reactant or manufactures, as a product or co-product, one or more of the organic hazardous air pollutants in Table 2.
			Table 4 HAP Content = The recirculating heat exchange system is not used exclusively to cool process fluids that contain less than 5 percent by weight of total HAPs listed in Table 4 of title 40 CFR Part 63, Subpart F.
			Alternate Means of Emission Limitation = No alternative means of emission limitation has been approved by the EPA Administrator to achieve a reduction in organic HAP emission or no alternate has been requested.
			NPDES Permit = The once-through heat exchange system is not subject to NPDES permit with an allowable discharge limit of 1 part per million or less above influent concentration or 10 percent or less above influent concentration.
			Meets 40 CFR 63.104(a)(4)(i)-(iv) = The once-through heat exchange system is not subject to an NPDES permit that meets 40 CFR § 63.104(a)(4)(i) - (iv).
			Heat Exchange System = A heat exchange system is utilized.
			Table 9 HAP Content = The once-through heat exchange system is not used exclusively to cool process fluids that contain less than 5 percent by weight of total HAPs listed in Table 9 of 40 CFR Part 63, Subpart G.
			Cooling Water Monitored = The cooling water is being monitored for the presence of one or more HAPs or other representative substances whose presence in cooling water indicates a leak.
			Cooling Water Pressure = The heat exchange system is not operated with the minimum pressure on the cooling water side at least 35 kilopascals greater than the maximum pressure on the process side.

<sup>\* -</sup> The "unit attributes" or operating conditions that determine what requirements apply

#### **NSR Versus Title V FOP**

The state of Texas has two Air permitting programs, New Source Review (NSR) and Title V Federal Operating Permits. The two programs are substantially different both in intent and permit content.

NSR is a preconstruction permitting program authorized by the Texas Clean Air Act and Title I of the Federal Clean Air Act (FCAA). The processing of these permits is governed by 30 Texas Administrative Code (TAC) Chapter 116.111. The Title V Federal Operating Program is a federal program authorized under Title V of the FCAA that has been delegated to the state of Texas to administer and is governed by 30 TAC Chapter 122. The major differences between the two permitting programs are listed in the table below:

NSR Permit	Federal Operating Permit (FOP)
Issued Prior to new Construction or modification of an existing facility	For initial permit with application shield, can be issued after operation commences; significant revisions require approval prior to operation.
Authorizes air emissions	Codifies existing applicable requirements, does not authorize new emissions
Ensures issued permits are protective of the environment and human health by conducting a health effects review and that requirement for best available control technology (BACT) is implemented.	Applicable requirements listed in permit are used by the inspectors to ensure proper operation of the site as authorized. Ensures that adequate monitoring is in place to allow compliance determination with the FOP.
Up to two Public notices may be required. Opportunity for public comment and contested case hearings for some authorizations.	One public notice required. Opportunity for public comments.  No contested case hearings.
Applies to all point source emissions in the state.	Applies to all major sources and some non-major sources identified by the EPA.
Applies to facilities: a portion of site or individual emission sources	One or multiple FOPs cover the entire site (consists of multiple facilities)
Permits include terms and conditions under which the applicant must construct and operate its various equipment and processes on a facility basis.	Permits include terms and conditions that specify the general operational requirements of the site; and also include codification of all applicable requirements for emission units at the site.
Opportunity for EPA review for Federal Prevention of Significant Deterioration (PSD) and Nonattainment (NA) permits for major sources.	Opportunity for EPA review, affected states review, and a Public petition period for every FOP.
Permits have a table listing maximum emission limits for pollutants	Permit has an applicable requirements table and Periodic Monitoring (PM) / Compliance Assurance Monitoring (CAM) tables which document applicable monitoring requirements.
Permits can be altered or amended upon application by company. Permits must be issued before construction or modification of facilities can begin.	Permits can be revised through several revision processes, which provide for different levels of public notice and opportunity to comment. Changes that would be significant revisions require that a revised permit be issued before those changes can be operated.
NSR permits are issued independent of FOP requirements.	FOPs are independent of NSR permits, but contain a list of all NSR permits incorporated by reference

# [ SEQ CHAPTER \h \r 1]New Source Review Requirements

Below is a list of the New Source Review (NSR) permits for the permitted area. These NSR permits are incorporated by reference into the operating permit and are enforceable under it. These permits can be found in the main TCEQ file room,

Page 16 of 20

located on the first floor of Building E, 12100 Park 35 Circle, Austin, Texas. In addition, many of the permits are accessible online through the link provided below. The Public Education Program may be contacted at 1-800-687-4040 or the Air Permits Division (APD) may be contacted at 1-512-239-1250 for help with any question.

Additionally, the site contains emission units that are permitted by rule under the requirements of 30 TAC Chapter 106, Permits by Rule. Permit by Rule (PBR) registrations submitted by permittees are also available online through the link provided below. The following table specifies the PBRs that apply to the site.

The TCEQ has interpreted the emission limits prescribed in 30 TAC §106.4(a) as both emission thresholds and default emission limits. The emission limits in 30 TAC §106.4(a) are all considered applicable to each facility as a threshold matter to ensure that the owner/operator qualifies for the PBR authorization. Those same emission limits are also the default emission limits if the specific PBR does not further limit emissions or there is no lower, certified emission limit claimed by the owner/operator.

This interpretation is consistent with how TCEQ has historically determined compliance with the emission limits prior to the addition of the "as applicable" language. The "as applicable" language was added in 2014 as part of changes to the sentence structure in a rulemaking that made other changes to address greenhouse gases and was not intended as a substantive rule change. This interpretation also provides for effective and practical enforcement of 30 TAC §106.4(a), since for the TCEQ to effectively enforce the emission limits in 30 TAC §106.4(a) as emission thresholds, all emission limits must apply. As provided by 30 TAC §106.4(a)(2) and (3), an owner/operator shall not claim a PBR authorization if the facility is subject to major New Source Review. The practical and legal effect of the language in 30 TAC § 106.4 is that if a facility does not emit a pollutant, then the potential to emit for that particular pollutant is zero, and thus, the facility is not authorized to emit the pollutant pursuant to the PBR.

The status of air permits, applications, and PBR registrations may be found by performing the appropriate search of the databases located at the following website:

[ HYPERLINK "http://www.tceq.texas.gov/permitting/air/nav/air\_status\_permits.html" ]

Details on how to search the databases are available in the **Obtaining Permit Documents** section below.

#### **New Source Review Authorization References**

Title 30 TAC Chapter 116 Permits, 8 Permits, or NA Permits) for the App	Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD blication Area.
Authorization No.: 36646	Issuance Date: 12/15/2009
Authorization No.: 5807A	Issuance Date: 12/05/2018
Permits By Rule (30 TAC Chapter 1	06) for the Application Area
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 11/01/2003
Number: 106.264	Version No./Date: 09/04/2000
Number: 106.371	Version No./Date: 09/04/2000
Number: 106.472	Version No./Date: 03/14/1997
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.478	Version No./Date: 09/04/2000

#### **Emission Units and Emission Points**

In air permitting terminology, any source capable of generating emissions (for example, an engine or a sandblasting area) is called an Emission Unit. For purposes of Title V, emission units are specifically listed in the operating permit when they have applicable requirements other than New Source Review (NSR), or when they are listed in the permit shield table.

The actual physical location where the emissions enter the atmosphere (for example, an engine stack or a sand-blasting yard) is called an emission point. For New Source Review preconstruction permitting purposes, every emission unit has an associated emission point. Emission limits are listed in an NSR permit, associated with an emission point. This list of emission points and emission limits per pollutant is commonly referred to as the "Maximum Allowable Emission Rate Table", or "MAERT" for short. Specifically, the MAERT lists the Emission Point Number (EPN) that identifies the emission point, followed immediately by the Source Name, identifying the emission unit that is the source of those emissions on this table.

Thus, by reference, an emission unit in a Title V operating permit is linked by reference number to an NSR authorization, and its related emission point.

#### **Monitoring Sufficiency**

Federal and state rules, 40 CFR § 70.6(a)(3)(i)(B) and 30 TAC § 122.142(c) respectively, require that each federal operating permit include additional monitoring for applicable requirements that lack periodic or instrumental monitoring (which may include recordkeeping that serves as monitoring) that yields reliable data from a relevant time period that are representative of the emission unit's compliance with the applicable emission limitation or standard. Furthermore, the federal operating permit must include compliance assurance monitoring (CAM) requirements for emission sources that meet the applicability criteria of 40 CFR Part 64 in accordance with 40 CFR § 70.6(a)(3)(i)(A) and 30 TAC § 122.604(b).

With the exception of any emission units listed in the Periodic Monitoring or CAM Summaries in the FOP, the TCEQ Executive Director has determined that the permit contains sufficient monitoring, testing, recordkeeping, and reporting requirements that assure compliance with the applicable requirements. If applicable, each emission unit that requires additional monitoring in the form of periodic monitoring or CAM is described in further detail under the Rationale for CAM/PM Methods Selected section following this paragraph.

#### **Obtaining Permit Documents**

The New Source Review Authorization References table in the FOP specifies all NSR authorizations that apply at the permit area covered by the FOP. Individual NSR permitting files are located in the TCEQ Central File Room (TCEQ Main Campus located at 12100 Park 35 Circle, Austin, Texas, 78753, Building E, Room 103). They can also be obtained electronically from TCEQ's Central File Room Online ([HYPERLINK "https://www.tceq.texas.gov/goto/cfr-online"]). Guidance documents that describe how to search electronic records, including Permits by Rule (PBRs) or NSR permits incorporated by reference into an FOP, archived in the Central File Room server are available at [HYPERLINK "https://www.tceq.texas.gov/permitting/air/nav/air\_status\_permits.html"]

All current PBRs are contained in Chapter 106 and can be viewed at the following website:

[ HYPERLINK "https://www.tceq.texas.gov/permitting/air/permitbyrule/air pbr index.html" ]

Previous versions of 30 TAC Chapter 106 PBRs may be viewed at the following website:

[ HYPERLINK "http://www.tceq.texas.gov/permitting/air/permitbyrule/historical rules/old106list/index106.html" ]

Historical Standard Exemption lists may be viewed at the following website:

[ HYPERLINK "http://www.tceq.texas.gov/permitting/air/permitbyrule/historical rules/oldselist/se index.html" ]

Additional information concerning PBRs is available on the TCEQ website:

Page 18 of 20

# **Compliance Review**

OP-UA36 - Steel Plant Unit Attributes

OP-UA37 - Basic Oxygen Process Furnace Unit Attributes

·	
Compliance History Review	
1. In accordance with 30 TAC Chapter 60, the compliance history was reviewed on April 6, 2020.	
Site rating: N/A Company rating: N/A	
(High < 0.10; Satisfactory ≥ 0.10 and ≤ 55; Unsatisfactory > 55)	
2. Has the permit changed on the basis of the compliance history or site/company rating?	No
Site/Permit Area Compliance Status Review	
Were there any out-of-compliance units listed on Form OP-ACPS?	Nο
2. Is a compliance plan and schedule included in the permit?	
Danneit naviance natare	
Permit reviewer notes:	
• The compliance ratings are shown N/A because the site is less than six months in operation due to the ownershi	р
change.	
Available Unit Attribute Forms	
OP-UA1 - Miscellaneous and Generic Unit Attributes	
OP-UA2 - Stationary Reciprocating Internal Combustion Engine Attributes	
OP-UA3 - Storage Tank/Vessel Attributes	
OP-UA4 - Loading/Unloading Operations Attributes	
OP-UA5 - Process Heater/Furnace Attributes	
OP-UA6 - Boiler/Steam Generator/Steam Generating Unit Attributes	
OP-UA7 - Flare Attributes	
OP-UA8 - Coal Preparation Plant Attributes	
OP-UA9 - Nonmetallic Mineral Process Plant Attributes	
OP-UA10 - Gas Sweetening/Sulfur Recovery Unit Attributes	
OP-UA11 - Stationary Turbine Attributes	
OP-UA12 - Fugitive Emission Unit Attributes	
OP-UA13 - Industrial Process Cooling Tower Attributes	
OP-UA14 - Water Separator Attributes	
OP-UA15 - Emission Point/Stationary Vent/Distillation Operation/Process Vent Attributes	
OP-UA16 - Solvent Degreasing Machine Attributes	
OP-UA17 - Distillation Unit Attributes	
OP-UA18 - Surface Coating Operations Attributes	
OP-UA19 - Wastewater Unit Attributes	
OP-UA20 - Asphalt Operations Attributes	
OP-UA21 - Grain Elevator Attributes	
OP-UA22 - Printing Attributes OP-UA24 - Wool Fiberglass Insulation Manufacturing Plant Attributes	
OP-UA24 - Wool Fiberglass Insulation Manufacturing Plant Attributes OP-UA25 - Synthetic Fiber Production Attributes	
OP-UA26 - Electroplating and Anodizing Unit Attributes	
OP-UA27 - Nitric Acid Manufacturing Attributes	
OP-UA28 - Polymer Manufacturing Attributes	
OP-UA29 - Glass Manufacturing Unit Attributes	
OP-UA30 - Kraft, Soda, Sulfite, and Stand-Alone Semichemical Pulp Mill Attributes	
OP-UA31 - Lead Smelting Attributes	
OP-UA32 - Copper and Zinc Smelting/Brass and Bronze Production Attributes	
OP-UA33 - Metallic Mineral Processing Plant Attributes	
OP-UA34 - Pharmaceutical Manufacturing	
OP-UA35 - Incinerator Attributes	

Page **19** of **20** 

- OP-UA38 Lead-Acid Battery Manufacturing Plant Attributes
- OP-UA39 Sterilization Source Attributes
- OP-UA40 Ferroalloy Production Facility Attributes
- OP-UA41 Dry Cleaning Facility Attributes
- OP-UA42 Phosphate Fertilizer Manufacturing Attributes
- OP-UA43 Sulfuric Acid Production Attributes
- OP-UA44 Municipal Solid Waste Landfill/Waste Disposal Site Attributes
- OP-UA45 Surface Impoundment Attributes
- OP-UA46 Epoxy Resins and Non-Nylon Polyamides Production Attributes
- OP-UA47 Ship Building and Ship Repair Unit Attributes
- OP-UA48 Air Oxidation Unit Process Attributes
- OP-UA49 Vacuum-Producing System Attributes
- OP-UA50 Fluid Catalytic Cracking Unit Catalyst Regenerator/Fuel Gas Combustion Device/Claus Sulfur Recovery Plant Attributes
- OP-UA51 Dryer/Kiln/Oven Attributes
- OP-UA52 Closed Vent Systems and Control Devices
- OP-UA53 Beryllium Processing Attributes
- OP-UA54 Mercury Chlor-Alkali Cell Attributes
- OP-UA55 Transfer System Attributes
- OP-UA56 Vinyl Chloride Process Attributes
- OP-UA57 Cleaning/Depainting Operation Attributes
- OP-UA58 Treatment Process Attributes
- OP-UA59 Coke By-Product Recovery Plant Attributes
- OP-UA60 Chemical Manufacturing Process Unit Attributes
- OP-UA61 Pulp, Paper, or Paperboard Producing Process Attributes
- OP-UA62 Glycol Dehydration Unit Attributes
- OP-UA63 Vegetable Oil Production Attributes